



● UTD1062C



● UTD1202C

SPECIFICATIONS

	UTD1062C	UTD1102C	UTD1202C
Bandwidth	60MHz	100MHz	200MHz
Channels	2		
Sampling rate	250MS/s	500MS/s	1GS/s
Rise time	≤5.8ns	≤3.5ns	≤1.8ns
Memory depth	7.5kpts		
Vertical sensitivity	5mV/div~50V/div		
Time base scale	5ns/div-50s/div		2ns/div-50s/div
Storage modes	Setup, waveform, bitmap		
Trigger modes	Edge, pulse width, video and alternative		
Interfaces	USB host, USB OTG (UTD1202C Optional)		
Multimeter Specifications	Range	Accuracy	
DC voltage (V)	600mV/6V/60V/600V/1000V	±(1%+5)	
AC voltage (V)(45Hz~400Hz)	600mV/6V/60V/600V/700V	±(1.2%+5), Frequency: <200Hz ±(1.5%+5), Frequency: ≥200Hz	
DC current (A)	6mA/60mA/600mA 6A	±(1.2%+5) ±(1.5%+5)	
AC current (A)(45Hz~400Hz)	6mA/60mA/600mA 6A	±(2%+5) ±(2.5%+5)	
Resistance (Ω)	6kΩ/60kΩ/600kΩ 600Ω/6MΩ/60MΩ	±(1.2%+5) ±(1.5%+5)	
Capacitance (F)	6nF/6mF 60nF/600nF/6μF/60μF/600μF	±(5%+10) ±(4%+5)	
Display count	6000		
Auto range	√		

GENERAL CHARACTERISTICS

Power	Li-ion battery: 7.4V 4400mAh; DC adapter: 100~240V 50/60Hz input, 9V/4A output
Display	5.7 inches TFT LCD, QVGA (320x240)
Product color	Red and grey
Product net weight	1.8kg
Product size	268mm x 168 mm x 60mm
Standard accessories	Probe x2 (1x, 10x switchable), current voltage converter, power cord, adapter, test leads, PC software CD
Standard individual packing	Carton box, carrying bag
Standard quantity per carton	4pcs
Standard carton measurement	500mm x 400mm x 320mm
Standard carton gross weight	16.7 kg